PATENT ABSTRACTS OF JAPAN

F01L 1/14

F01L

(11)Publication number:

2000-038906

(43) Date of publication of application: 08.02.2000

1/18

(51)Int.CI.

(71)Applicant: NIPPON SEIKO KK

(21)Application number: 10-204821 21.07.1998 (22)Date of filing:

(72)Inventor: YAMAMOTO TOSHIYUKI


(54) CAM FOLLOWER FOR VALVE SYSTEM IN ENGINE

(57) Abstract:

PROBLEM TO BE SOLVED: To facilitate the design of a cam follower for a valve system in an engine capable of ensuring sufficient durability by restricting the maximum value of bending stress acted on a shaft in association with rotation of a camshaft to a

specialized value or less.

SOLUTION: A hollow pipe shaped shaft 5 is fixed between a pair of supporting wall parts in a hooking condition. A roller 6 is directly supported around the shaft 5, or it is rotatably supported through a radial roller bearing 9. The maximum value of bending stress acted on the shat 5 is restricted to 1.5 kgf/mm2 or less. It is thus possible to prevent the damage such as cracking from generating on the shaft 5, before a life of an engine attains the longest life (about 2,000,000 km in a traveling distance). Since the maximum value of the bending stress is restricted to a constant rate, it is possible to facilitate the design of the cam follower for the valve system in the engine having sufficient durability.



LEGAL STATUS

[Date of request for examination]

[Date of sending the examiner's decision of rejection]

[Kind of final disposal of application other than the examiner's decision of rejection or application converted registration]

[Date of final disposal for application]

[Patent number]

[Date of registration]

[Number of appeal against examiner's decision of rejection]

[Date of requesting appeal against examiner's decision of rejection]

[Date of extinction of right]

(19)日本国特許庁 (JP)

(12) 公開特許公報(A)

(11)特許出願公開番号 特開2000-38906 (P2000-38906A)

(43)公開日 平成12年2月8日(2000.2.8)

(51) Int.Cl.'	酸別記号	FI	テーマコード(容考)
F01L 1/14		F01L 1/14	E 3G016
1/18		1/18	B N
		· .	M
		審查請求 未請求	請求項の数1 OL (全 4 頁)
(21)出願番号	特顏平10-204821	(71)出願人 0000042 日本精	04
(22)出願日	平成10年7月21日(1998.7.21)	東京都品 (72)発明者 山本 領神奈川県	品川区大崎1丁目6番3号
			小山 武男 (外1名)
* ·		Fターム(参考) 300	16 AAO6 AA19 BA25 BA34 BB22 CA12 CA13 CA22 CA32 EA02 EA24 FA16 CA00 GA05
9			1.

(54) 【発明の名称】 エンジンの動弁機構用カムフォロア装置

(57) 【要約】

【課題】 カムからローラ6を介して軸5に加わるラジアル荷重に基づいて、この軸5に加わる曲げ応力に拘らず、この軸5の損傷防止を図る。

【解決手段】 上記曲げ応力の値の最大値を、15 kgf/mm² 以下に規制する。通常考えられるエンジンの寿命以前に、上記軸5 に亀裂等の損傷が発生するのを防止できる設計を、容易に行なえる。

